CLASSIC LIGHTING PEDESTAL



The **CLASSIC** LIGHTING PEDESTAL Range

A range of versatile galvanised steel pedestals with composite or metal outer skins.

PRODUCT FEATURES

- Hot-dipped galvanised steel internal chassis
- UV stabilised external shell and shell material variants: steel, composite or aluminium
- 360 degree low energy LED lighting
- Fully segregated lighting compartment
- Height and width variants
- Designed for ease of installation and maintenance












SPECIFICATIONS

CHARACTERISTICS

| Materials | Head: ABS Granulate Natural Polyethylene Body Internal: Hot-Dipped Galvanised Steel Body External: Powder Coated Aluminium / Aluminium Composite / 304 Stainless Steel BS EN-10204:2004, BS EN 573-3:2013, BS EN 755-2:2016 |
|-----------------------|--|
| Dimensions | A: 750mm, 1000mm B: 885mm, 1135mm C: 205mm D: 185mm E: 135mm |
| Operating Temperature | -30°C to +60°C (Installed and Operated Within Multiple Climates from Around the Globe) |
| IP Rating | IP65 |
| Compliances | BS7671 Wiring Regulations BS EN 61439-2:2011, BS EN 61439-5:2015 CE Certified Low Voltage Directive 2014/35/EU Electromagnetic Directive 2014/30/EU Powder Coated Corrosion Resistant / Salt Mist Tested Panels ISO 9227 UV Stabilised Flame Retardant to UL94 |
| Typical Weight (AVG) | 12-15kg (Standard 750mm) |

360 Degree Low Energy LED

4300k 4x1 Watt 6amp RCBO





Ė.



Rating

- Shell colours and materials
- Photocell controlled lighting

- Branding vinyls
- Switching and control
- LED Colours



Images are for marketing purposes only and are not contractual © 2019



Head office contact: t: +44 (0) 1205 724754 f: +44 (0) 1205 724876 rolec@rolecserv.co.uk Rolec Services Ltd Ralphs Lane, Frampton West Boston, Lincolnshire UK. PE20 1QU ™®RolecMarina www.rolecserv.com